

Package ‘acled.api’

January 10, 2024

Title Automated Retrieval of ACLED Conflict Event Data

Version 1.1.7

Date 2023-12-24

Author Christoph Dworschak [aut, cre]

(<https://orcid.org/0000-0003-0196-9545>),

Rob Williams [ctb] (<https://orcid.org/0000-0001-9259-3883>)

Maintainer Christoph Dworschak <dworschak@posteo.de>

Description Access and manage the application programming interface (API) of the Armed Conflict Location & Event Data Project (ACLED) at <https://acleddata.com/>. The package makes it easy to retrieve a user-defined sample (or all of the available data) of ACLED, enabling a seamless integration of regular data updates into the research work flow. It requires a minimal number of dependencies. See the package's README file for a note on replicability when drawing on ACLED data. When using this package, you acknowledge that you have read ACLED's terms and conditions of use, and that you agree with their attribution requirements.

URL <https://gitlab.com/chris-dworschak/acled.api>

License CC BY-NC 4.0

Encoding UTF-8

Language en-US

RoxygenNote 7.2.3

Imports httr, jsonlite

Suggests testthat

NeedsCompilation no

Repository CRAN

Date/Publication 2024-01-10 12:33:02 UTC

R topics documented:

acled.api	2
get.api.regions	4

Index	6
--------------	----------

Description

Access and manage the application programming interface (API) of the **Armed Conflict Location & Event Data Project (ACLED)**. The function `acled.api()` makes it easy to retrieve a user-defined sample (or all of the available data) of ACLED, enabling a seamless integration of regular data updates into the research work flow. If the data are intended for replicable use (e.g., later publication of analysis results), the downloaded data should be stored locally after retrieval. See the package's README file for a note on replicability when using ACLED data.

When using this package, you acknowledge that you have read ACLED's terms and conditions of use, and that you agree with their attribution requirements.

Usage

```
acled.api(  
  email.address = Sys.getenv("ACLED_EMAIL_ADDRESS"),  
  access.key = Sys.getenv("ACLED_ACCESS_KEY"),  
  country = NULL,  
  region = NULL,  
  start.date = NULL,  
  end.date = NULL,  
  add.variables = NULL,  
  all.variables = FALSE,  
  dyadic = FALSE,  
  interaction = NULL,  
  other.query = NULL  
)
```

Arguments

- `email.address` character string. Supply the email address that you registered with **ACLED access**. The email address can also be set as an environment variable using `Sys.setenv(ACLED_EMAIL_ADDRESS="your.email.address")`, in which case this argument can be skipped. Usage examples below illustrate these two approaches.
- `access.key` character string. Supply your ACLED access key. The access key can also be set as an environment variable using `Sys.setenv(ACLED_ACCESS_KEY="your.access.key")`, in which case this argument can be skipped. Usage examples below illustrate these two approaches.
- `country` character vector. Supply one or more country names to narrow down which events should be retrieved. See the details below for information on how the arguments "country" and "region" interact.

region	numeric or character vector. Supply one or more region codes (numeric) or region names (character) to narrow down which events should be retrieved (see ACLED's API user guide for details on region codes and names). See the details below for information on how the arguments "country" and "region" interact.
start.date	character string. Supply the earliest date to be retrieved. Format: "yyyy-mm-dd".
end.date	character string. Supply the last date to be retrieved. Format: "yyyy-mm-dd".
add.variables	character vector. Supply the names of ACLED variables you wish to add to the default output (see ACLED's codebook for details). The default output includes: region, country, year, event_date, source, admin1, admin2, admin3, location, event_type, sub_event_type, interaction, fatalities.
all.variables	logical. When set to FALSE (default), a narrow default selection of variables is returned (which can be refined using the argument add.variables). If set to TRUE, all variables are included in the output (overrides argument add.variables).
dyadic	logical. When set to FALSE (default), monadic data is returned (one observation per event). If set to TRUE, dyadic data is returned.
interaction	numeric vector. Supply one or more interaction codes to narrow down which events should be retrieved (see ACLED's codebook for details).
other.query	character vector. Allows users to add their own ACLED API queries to the GET call. Vector elements are assumed to be individual queries, and are automatically separated by an & sign.

Details

The function `acled.api()` is an R wrapper for the [Armed Conflict Location & Event Data Project](#) API. Internally it uses `httr` to access the API, and `jsonlite` to manage the JSON content that the call returns. The JSON data are converted into the base class `data.frame`. Variables are of class `character` by default. Variables which only contain numbers as recognized by the regular expression `^[0-9]+$` are coerced into `numeric` before the `data.frame` object is returned.

The user's registered email address and ACLED access key can be supplied as strings directly to their respective arguments, or set in advance as environment variables using

```
Sys.setenv(ACLED_EMAIL_ADDRESS="your.email.address") and
```

```
Sys.setenv(ACLED_ACCESS_KEY="your.access.key").
```

If both the `country` argument and the `region` argument are `NULL` (default), all available countries are retrieved. The same applies to the time frame when both the `start.date` and the `end.date` are `NULL` (default). Note that the API cannot handle requests with only one of the dates specified (either none of them or both of them need to be supplied).

The ACLED API combines the `country` argument and the `region` argument with a logical AND operator. Therefore, specifying e.g. the `country` "Togo" and the `region` "Southern Africa" leads the API to query for a country named "Togo" in the region "Southern Africa". In this case, no data will be returned as no events match this query.

Value

A data frame containing ACLED events.

Author(s)

Christoph Dworschak

Website: <https://www.chrisdworschak.com/>

References

Armed Conflict Location & Event Data Project (ACLED); <https://acleddata.com/>
Clionadh Raleigh, Andrew Linke, Havard Hegre and Joakim Karlsen. 2010. "Introducing ACLED-
Armed Conflict Location and Event Data." *Journal of Peace Research* 47 (5): 651-660.

Examples

```
## Not run:
# Email and access key provided as strings:
my.data.frame1 <- acled.api(
  email.address = "your.email.address",
  access.key = "your.access.key",
  region = c(1,7),
  start.date = "2018-11-01",
  end.date = "2018-11-31")
head(my.data.frame1)

# Email and access key provided as environment variables:
my.data.frame2 <- acled.api(
  email.address = Sys.getenv("ACLED_EMAIL_ADDRESS"),
  access.key = Sys.getenv("ACLED_ACCESS_KEY"),
  region = c(1,7),
  start.date = "2020-01-01",
  end.date = "2020-11-31",
  interaction = c(10:18, 22:28),
  add.variables = c("geo_precision", "time_precision"))
sd(my.data.frame2$geo_precision)

## End(Not run)
```

get.api.regions

ACLED API region support function

Description

List of region names and codes as they are supplied by the [ACLED API user guide](#).

Usage

```
get.api.regions()
```

Details

This single-purpose support function does not take arguments. It is set up as a convenient way to return region names and region codes to be used in the `acled.api()` main function's region argument.

Value

A list of length 2.

1. A data frame object containing ACLED region names and codes.
2. A string with version information.

Author(s)

Christoph Dworschak

Website: <https://www.chrisdworschak.com/>

References

Armed Conflict Location & Event Data Project (ACLED) [API user guide](#)
Clionadh Raleigh, Andrew Linke, Havard Hegre and Joakim Karlsen. 2010. "Introducing ACLED-Armed Conflict Location and Event Data." *Journal of Peace Research* 47 (5): 651-660.

Index

`acled.api`, 2

`get.api.regions`, 4