

Package ‘survRM2’

October 14, 2022

Type Package

Title Comparing Restricted Mean Survival Time

Version 1.0-4

Date 2022-06-13

Author Hajime Uno, Lu Tian, Miki Horiguchi, Angel Cronin, Chakib Battioui, James Bell

Maintainer Hajime Uno <huno@jimmy.harvard.edu>

Depends survival

Description Performs two-sample comparisons using the restricted mean survival time (RMST) as a summary measure of the survival time distribution. Three kinds of between-group contrast metrics (i.e., the difference in RMST, the ratio of RMST and the ratio of the restricted mean time lost (RMTL)) are computed. It performs an ANCOVA-type covariate adjustment as well as unadjusted analyses for those measures.

License GPL-2

RoxygenNote 7.2.0.9000

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2022-06-14 03:50:02 UTC

R topics documented:

survRM2-package	2
plot.rmst2	3
print.rmst2	4
rmst2	4
rmst2.sample.data	6

Index	8
--------------	----------

Description

Performs two-sample comparisons using the restricted mean survival time (RMST) as a summary measure of the survival time distribution. Three kinds of between-group contrast metrics (i.e., the difference in RMST, the ratio of RMST and the ratio of the restricted mean time lost (RMTL)) are computed. The package has a function to perform an ANCOVA-type covariate adjustment as well as unadjusted analyses for those measures.

Author(s)

Hajime Uno, Lu Tian, Miki Horiguchi, Angel Cronin, Chakib Battioui, James Bell
Maintainer: Hajime Uno <huno@jimmy.harvard.edu>

References

Uno H, Claggett B, Tian L, Inoue E, Gallo P, Miyata T, Schrag D, Takeuchi M, Uyama Y, Zhao L, Skali H, Solomon S, Jacobus S, Hughes M, Packer M, Wei LJ. Moving beyond the hazard ratio in quantifying the between-group difference in survival analysis. *Journal of clinical Oncology* 2014, 32, 2380-2385. doi:10.1200/JCO.2014.55.2208.

Tian L, Zhao L, Wei LJ. Predicting the restricted mean event time with the subject's baseline covariates in survival analysis. *Biostatistics* 2014, 15, 222-233. doi:10.1093/biostatistics/kxt050.

See Also

survival

Examples

```
#--- sample data ---#
D=rmst2.sample.data()
time=D$time
status=D$status
arm=D$arm
tau=NULL
x=D[,c(4,6,7)]
#--- without covariates ----
a=rmst2(time, status, arm, tau=10)
print(a)
plot(a, xlab="Years", ylab="Probability", density=60)
#--- with covariates ----
a=rmst2(time, status, arm, tau=10, covariates=x)
print(a)
```

`plot.rmst2`*plot.rmst2*

Description

S3 method for class 'rmst2'

Usage

```
## S3 method for class 'rmst2'  
plot(  
  x,  
  xlab = "",  
  ylab = "",  
  col = "red",  
  col.RMST = "pink",  
  col.RMTL = "orange",  
  density = 80,  
  angle = 85,  
  ...  
)
```

Arguments

<code>x</code>	Results of the unadjusted analyses.
<code>xlab</code>	x label.
<code>ylab</code>	y label.
<code>col</code>	Color for line. Default is red.
<code>col.RMST</code>	Color for areas of RMST. Default is pink.
<code>col.RMTL</code>	Color for areas of RMTL. Default is orange.
<code>density</code>	Density of shading lines, in lines per inch. Default is 80.
<code>angle</code>	Slope of shading lines, given as an angle in degrees (counter-clockwise). Default is 85.
<code>...</code>	Further arguments ignored in this function.

Value

returns a plot

print.rmst2	<i>print.rmst2</i>
-------------	--------------------

Description

S3 method for class 'rmst2'

Usage

```
## S3 method for class 'rmst2'
print(x, digits = 3, ...)
```

Arguments

x	Object to be printed.
digits	Integer indicating the number of decimal places.
...	Further arguments ignored in this function.

Value

returns summary output for class 'rmst2'

rmst2	<i>Comparing restricted mean survival time</i>
-------	------------------------------------------------

Description

Performs two-sample comparisons using the restricted mean survival time (RMST) as a summary measure of the survival time distribution. Three kinds of between-group contrast metrics (i.e., the difference in RMST, the ratio of RMST and the ratio of the restricted mean time lost (RMTL)) are computed. The Greenwood plug-in estimator is used for the asymptotic variance. It performs ANCOVA-type adjusted analyses when covariates are passed to it as an argument.

Usage

```
rmst2(time, status, arm, tau = NULL, covariates = NULL, alpha = 0.05)
```

Arguments

time	The follow-up time for right censored data.
status	The status indicator, 1=event, and 0=right censored.
arm	The group indicator for comparison. The elements of this vector take either 1 or 0. Normally, 0=control group, 1=active treatment group.

<code>tau</code>	A scalar value to specify the truncation time point for the RMST calculation. When <code>tau = NULL</code> , the default value is used. See Details for the definition of the default <code>tau</code> .
<code>covariates</code>	This specifies covariates to be used for the adjusted analyses. When <code>NULL</code> , unadjusted analyses are performed. When non <code>NULL</code> , the ANCOVA-type adjusted analyses are performed using those variables passed as <code>covariates</code> . This can be one variable (vector) or more than one variables (matrix).
<code>alpha</code>	The default is 0.05. $(1-\alpha)$ confidence intervals are reported.

Details

The definition of the default `tau`. Let x_1 and x_0 be the maximum observed time in Group 1 and Group 0, respectively. Case 1: if the last observations in Group 1 and Group 0 are "event," then $\tau = \max(x_1, x_0)$. Case 2-1: if the last observation in Group 1 is "event," the last observation in Group 0 is "censor," and $x_1 \leq x_0$, $\tau = \max(x_1, x_0) = x_0$. Case 2-2: if the last observation in Group 0 is "event," the last observation in Group 1 is "censor," and $x_1 > x_0$, $\tau = \max(x_1, x_0) = x_1$. Case 3-1: if the last observation in Group 1 is "event," the last observation in Group 0 is "censor," and $x_1 > x_0$, $\tau = \min(x_1, x_0) = x_0$. Case 3-2: if the last observation in Group 0 is "event," the last observation in Group 1 is "censor," and $x_1 \leq x_0$, $\tau = \min(x_1, x_0) = x_1$. Case 4: the last observations in Group 1 and Group 0 are "censor," then $\tau = \min(x_1, x_0)$.

Value

an object of class `rmst2`.

<code>tau</code>	the truncation time used in the analyses
<code>note</code>	a note regarding the truncation time
<code>RMST.arm1</code>	RMST results in arm 1. This is generated only when <code>covariates</code> is not specified.
<code>RMST.arm0</code>	RMST results in arm 0. This is generated only when <code>covariates</code> is not specified.
<code>unadjusted.result</code>	Results of the unadjusted analyses. This is generated only when <code>covariates</code> is not specified.

The values below are generated when some covariates are passed to the function.

<code>adjusted.result</code>	Results of the adjusted analyses.
<code>RMST.difference.adjusted</code>	Results of the parameter estimates with the model to derive an adjusted difference in RMST.
<code>RMST.ratio.adjusted</code>	Results of the parameter estimates with the model to derive an adjusted ratio of RMST.
<code>RMTL.ratio.adjusted</code>	Results of the parameter estimates with the model to derive an adjusted ratio of RMTL.

Author(s)

Hajime Uno, Lu Tian, Miki Horiguchi, Angel Cronin, Chakib Battioui, James Bell

References

Uno H, Claggett B, Tian L, Inoue E, Gallo P, Miyata T, Schrag D, Takeuchi M, Uyama Y, Zhao L, Skali H, Solomon S, Jacobus S, Hughes M, Packer M, Wei LJ. Moving beyond the hazard ratio in quantifying the between-group difference in survival analysis. *Journal of clinical Oncology* 2014, 32, 2380-2385. doi:10.1200/JCO.2014.55.2208.

Tian L, Zhao L, Wei LJ. Predicting the restricted mean event time with the subject's baseline covariates in survival analysis. *Biostatistics* 2014, 15, 222-233. doi:10.1093/biostatistics/kxt050.

Examples

```
#--- sample data ---#
D=rmst2.sample.data()
time=D$time
status=D$status
arm=D$arm
tau=NULL
x=D[,c(4,6,7)]
#--- without covariates ----
a=rmst2(time, status, arm, tau=10)
print(a)
plot(a, xlab="Years", ylab="Probability", density=60)
#--- with covariates ----
a=rmst2(time, status, arm, tau=10, covariates=x)
print(a)
```

rmst2.sample.data	<i>Generate a sample data from the pbc data</i>
-------------------	-------------------------------------------------

Description

This is a function to retrieve 312 randomized patients from the pbc data.

Usage

```
rmst2.sample.data(t.unit="year")
```

Arguments

t.unit Specify the time unit. It supports "year" (default), "month", and "day".

Details

The function creates a sample dataset to illustrate the usage of the function `rmst2()` in this package. The original pbc data in survival package consists of 418 patients data. This function loads the pbc data, select the 312 patients who were randomized. The status variable is edited, so that 1 indicates death and 0 indicates alive.

rmst2.sample.data

7

Value

returns a data frame

See Also

pbcr in survival package

Examples

```
D=rmst2.sample.data()  
head(D)
```

Index

* **survival**

survRM2-package, [2](#)

plot.rmst2, [3](#)

print.rmst2, [4](#)

rmst2, [4](#)

rmst2.sample.data, [6](#)

survRM2-package, [2](#)